



## MMATS Procast 10 Dual 4 ohm

Theil/Small	Dual 4 ohm	Dual 2 ohm
Znom=	2.000 ê	N/A
Sd=	0.0335 sqM	N/A
Fi=	26.958 Hz	N/A
Revc=	1.800 ê	N/A
Fo=	27.481 Hz	N/A
Krm=	0.543 mê	N/A
Vas=	59.3780 Litr	N/A
Qms=	11.786	N/A
Xmx=	11.1250 mM	N/A
Kxm=	0.052 mH	N/A
Cms=	372.5956 uM/N	N/A
Qes=	0.347	N/A
Cmx=	11.1250 mM	N/A
Erm=	1.104	N/A
Mms=	90.0200 Gram	N/A
Qts=	0.337	N/A
Exm=	0.564	N/A
Mmd=	86.4944 Gram	N/A
Pmx=	250.0 Wrms	N/A
SPLo	87.39 dB	N/A



Model	Sealed (Net)	Vented (Net)	Port Specs	Port Disp	Woofer Disp
Procast 10	<u>1.25cu</u>	1.50 cu.ft	12.56 sq." X 11" Long	.08 cu.ft	.12 cu.ft.

Hole Cutout Diameter	9.125"
Overall Diameter	10.5"
Mounting Depth	5.875"

**\*\* Enclosure Size is NET Interior Volume, EXCLUDING speaker and port displacement!!**

**3" round port equals 7.07 sq. inches**

**4" round port equals 12.56 sq. inches**

**6" round port equals 28.26 sq. inches**

