



MMATS Procast 12 Dual 4 ohm

Theil/Small	Dual 4 ohm	Dual 2 ohm
Znom=	2.000 ê	N/A
Sd=	0.0457 sqM	N/A
Fi=	26.581 Hz	N/A
Revc=	1.800 ê	N/A
Fo=	27.171 Hz	N/A
Krm=	0.005 mê	N/A
Vas=	81.2780 Litr	N/A
Qms=	9.058	N/A
Xmx=	9.6250 mM	N/A
Kxm=	0.049 mH	N/A
Cms=	274.0580 uM/N	N/A
Qes=	0.385	N/A
Cmx=	9.6250 mM	N/A
Erm=	1.141	N/A
Mms=	125.1990 Gram	N/A
Qts=	0.369	N/A
Exm=	0.609	N/A
Mmd=	119.5815 Gram	N/A
Pmx=	600.000 Wrms	N/A
SPLo	92.118 db	N/A



Model	Sealed (Net)	Vented (Net)	Port Specs	Port Disp	Woofer Disp
Procast 12	<u>1.5 cu. ft</u>	2.50 cu.ft	30 sq." X 15" Long	.26 cu.ft	.15 cu.ft.

Hole Cutout Diameter	11.187"
Overall Diameter	12 5/8
Mounting Depth	6"

**** Enclosure Size is NET Interior Volume, EXCLUDING speaker and port displacement!!**

3" round port equals 7.07 sq. inches

4" round port equals 12.56 sq. inches

6" round port equals 28.26 sq. inches

