



## MMATS Pro 15 Dual 4 ohm

Theil/Small	Dual 4 ohm	Dual 2 ohm
Znom=	2.000 ê	N/A
Sd=	0.0824 sqM	N/A
Fi=	19.894 Hz	N/A
Revc=	1.800 ê	N/A
Fo=	20.636 Hz	N/A
Krm=	0.000 mêm	N/A
Vas=	320.8210 Litr	N/A
Qms=	9.569	N/A
Xmx=	11.1250 mM	N/A
Kxm=	0.031 mH	N/A
Cms=	332.7440 uM/N	N/A
Qes=	0.268	N/A
Cmx=	11.1250 mM	N/A
Erm=	1.135	N/A
Mms=	178.7560 Gram	N/A
Qts=	0.261	N/A
Exm=	0.648	N/A
Mmd=	165.1554 Gram	N/A
Pmx=	400.000 Wrms	N/A
SPLo	92.11 dB	N/A



Model	Sealed (Net)	Vented (Net)	Port Specs	Port Disp	Woofers Disp
Pro 15	<u>2.0 cu. ft</u>	3.00 cu.ft	35 sq." X 14" Long	.24 cu.ft	.16 cu.ft.

Hole Cutout Diameter	13 7/8"
Overall Diameter	15 5/8"
Mounting Depth	7.125"

**\*\* Enclosure Size is NET Interior Volume, EXCLUDING speaker and port displacement!!**

**3" round port equals 7.07 sq. inches**

**4" round port equals 12.56 sq. inches**

**6" round port equals 28.26 sq. inches**

